



HDi 21K400 TC

UNIQUE BENEFITS

- Adaptive inductance field reading (autotuning)
- Electronic safety protection
- Heating temperature level setting
- User friendly color touch control panel 7"
- Long inductor cable 4.25 m
- **Plug and Play** with art. IND16kW/S inductor head



10+
inductor
heads extra
on request

**INDUCTOR
HEAD
HANDLE
INCLUDED**



ART - HDi 21K400 TC

APPLICATIONS

The HDi 21K400 TC heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding
- Bending
- Hardening
- Annealing

OPTIONALS



TIMER



HEAT
SENSOR IRT



PEDAL SWITCH



SHS



WIFI

CUSTOMIZATION ON REQUEST

Technical features



600x600x1140h mm



800x850x1350h mm



140 KG



Input power 21 kW - 32 A
Electrical connection IEC60309



400V/3PH+T 50



Working frequency 15-30 KHz



8 m Network cable



IP 21 Degree of protection



Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan



CE EAC UK CA Directives and Certification